

AC-Motoren GmbH

Graugussmotoren / Cast Iron Housing

Technische Daten / Technical data

8 polig Leerlaufdrehzahl 750 U/min - 8 pole Synchronous speed 750 rpm											400V / 50 Hz	
ACM 160 MA-8	4,00 / 4,80	720 / 864	81,00	0,73	9,76	53,06	6,00	1,90	2,00	0,07530	105,0	
ACM 160 MB-8	5,50 / 6,60	720 / 864	83,00	0,74	12,90	72,59	6,00	2,00	2,00	0,09310	115,0	
ACM 160 L-8	7,50 / 9,00	720 / 864	85,50	0,75	16,90	99,50	6,00	2,00	2,00	0,12600	145,0	
ACM 180 L-8	11,00 / 13,20	730 / 876	87,50	0,76	23,90	143,90	6,00	2,00	2,00	0,20300	160,0	
ACM 200 L-8	15,00 / 18,00	730 / 876	88,00	0,76	32,40	196,23	6,60	2,00	2,00	0,39900	228,0	
ACM 225 S-8	18,50 / 22,20	730 / 876	90,00	0,76	39,00	242,02	6,60	1,90	2,00	0,49100	242,0	
ACM 225 M-8	22,00 / 26,40	730 / 876	90,50	0,78	45,00	287,81	6,60	1,90	2,00	0,54700	265,0	
ACM 250 M-8	30,00 / 36,00	735 / 882	91,00	0,79	60,20	382,47	6,60	1,90	2,00	0,83400	368,0	
ACM 280 S-8	37,00 / 44,40	735 / 882	91,50	0,79	73,90	484,04	6,60	1,90	2,00	1,93000	472,0	
ACM 280 M-8	45,00 / 54,00	735 / 882	92,00	0,79	89,40	580,74	6,60	1,80	2,00	3,65000	538,0	
ACM 315 S-8	55,00 / 66,00	735 / 882	92,80	0,81	106,00	709,80	6,60	1,80	2,00	4,79000	900,0	
ACM 315 M-8	75,00 / 90,00	735 / 882	93,00	0,81	144,00	967,91	6,60	1,80	2,00	5,58000	1000,0	
ACM 315 LA-8	90,00 / 108,00	735 / 882	93,80	0,82	169,00	1161,49	6,60	1,80	2,00	6,37000	1055,0	
ACM 315 LB-8	110,00 / 132,00	735 / 882	94,00	0,82	206,00	1419,60	6,40	1,80	2,00	7,23000	1118,0	
ACM 355 MA-8	132,00 / 158,40	740 / 888	93,70	0,82	248,00	1692,08	6,40	1,80	2,00	7,90000	2000,0	
ACM 355 MB-8	160,00 / 192,00	740 / 888	94,20	0,82	299,00	2051,00	6,40	1,80	2,00	10,30000	2150,0	
ACM 355 L-8	200,00 / 240,00	740 / 888	94,50	0,83	368,00	2563,38	6,40	1,80	2,00	12,30000	2250,0	
ACM 400 MA-8	250,00 / 300,00	745 / 894	95,30	0,84	455,00	3205,00	6,29	1,85	2,48	25,63000	2914,0	
ACM 400 MB-8	280,00 / 336,00	745 / 894	95,30	0,84	503,00	3594,00	5,90	1,71	2,31	26,52000	3970,0	
ACM 400 LA-8	315,00 / 378,00	745 / 894	95,50	0,85	566,00	4038,00	6,13	1,81	2,38	27,86000	3392,0	
ACM 400 LB-8	355,00 / 426,00	745 / 894	95,60	0,85	641,00	4557,00	5,84	1,72	2,25	29,76000	3592,0	
ACM 400 LC-8	400,00 / 480,00	745 / 894	95,60	0,85	723,00	5128,00	6,39	1,96	2,44	31,34000	3949,0	
ACM 450 MA-8	315,00 / 378,00	746 / 895	95,40	0,82	583,00	4020,00	5,95	1,76	2,49	59,50000	3840,0	
ACM 450 MB-8	355,00 / 426,00	745 / 894	95,50	0,82	651,00	4520,00	5,67	1,66	2,35	64,50000	4090,0	
ACM 450 LA-8	400,00 / 480,00	745 / 894	95,70	0,83	729,00	5102,00	5,51	1,62	2,26	69,40000	4350,0	
ACM 450 LB-8	450,00 / 540,00	745 / 894	95,70	0,83	817,00	5740,00	5,43	1,62	2,18	75,20000	4660,0	
ACM 450 LC-8	500,00 / 600,00	745 / 894	95,70	0,83	913,00	6675,00	5,65	1,74	2,23	79,30000	4870,0	

Technische Änderungen und Irrtümer vorbehalten. / Technical modifications reserved, errors excepted.